

OMEGA VRF TECHNOLOGY

Engineered to elevate efficiency and comfort
..... to the next level!

VEWM SERIES

HIGH WALL VRF Indoor Unit Inverter Heat Pump 50Hz

Cooling Capacity Min~Max: 7,500~24,250 Btuh (2.2~7.1 kW)
Heating Capacity Min~Max: 8,540~25,615 Btuh (2.5~7.5 kW)

Product Features

- ✓ Whisper Quiet Design.
- ✓ Auto Restart.
- ✓ Washable Filter.
- ✓ Self Diagnostics Function.
- ✓ Factory Tested.
- ✓ Auto Swing (Vertical).
- ✓ Easy Installation & Maintenance

Indoor Unit Features

- ✓ Wireless LCD Remote Control (Standard).
- ✓ Wired LCD Remote Control (Optional).
- ✓ Deluxe Wired Controller with Weekly Timer (Optional).
- ✓ Centralized Controller (Optional).
- ✓ Smart Zone Controller (Optional).
- ✓ Remote Monitoring Software (Optional).
- ✓ Anti-Freezing Protection.
- ✓ Fan Motor Overload Protection.
- ✓ Temperature Sensor Malfunction.
- ✓ Cold Air Prevention Design (Heating Mode).



OMEGA



ISO 14001 ISO 9001

OTEC
AIR CONDITIONING

A Product of
OMEGA
Environmental
Technologies LLC.

OMEGA VRF TECHNOLOGY

Engineered to elevate efficiency and comfort
..... to the next level!

VEWM SERIES HIGH WALL VRF Indoor Unit Inverter Heat Pump 50Hz

Cooling Capacity Min~Max: 7,500~24,250 Btuh (2.2~7.1 kW)
Heating Capacity Min~Max: 8,540~25,615 Btuh (2.5~7.5 kW)

HIGH WALL VRF Indoor Unit

MODEL NO.	VEWM	008Q	010Q	012Q	015Q	017Q	019Q	022Q	024Q
		3A-RWV022	3A-RWV028	3A-RWV036	3A-RWV045	3A-RWV050	3A-RWV056	3A-RWV063	3A-RWV071
Cooling Capacity	Btuh (kw)	7,500 (2.2)	9,565 (2.8)	12,300 (3.6)	15,370 (4.5)	17,055 (5.0)	19,125 (5.6)	21,515 (6.3)	24,250 (7.1)
Heating Capacity	Btuh (kw)	8,540 (2.5)	10,950 (3.2)	13,660 (4.0)	17,055 (5.0)	19,810 (5.8)	21,515 (6.3)	23,910 (7.0)	25,615 (7.5)
Refrigerant Control		Electronic Expansion Valve @ Indoor Unit							
Coil Type		Grooved Cooper Tubes - Aluminum Blue Slit Fin							
Electrical	Voltage-Phase	220/240-1							
	Frequency	50HZ							
	FLA	0.22	0.22	0.27	0.27	0.27	0.32	0.32	0.32
	Input (W)	50	50	60	60	60	70	70	70
Air Filter		Cleanable Cartridge Type							
Fan	Type	Cross-Flow Fan							
	Speed	3-Speed							
	Qty	1	1	1	1	1	1	1	1
	Air Flow CFM (m³/hr) (Hi)	295 (500)	295 (500)	375 (630)	375 (630)	375 (630)	445 (750)	445 (750)	445 (750)
	Noise Level Hi (db)	38	38	44	44	44	44	44	44
Refrigerant Connections inches (mm)	Type	Flare							
	Liquid	1/4 (6.35)	1/4 (6.35)	1/4 (6.35)	1/4 (6.35)	1/4 (6.35)	3/8 (9.52)	3/8 (9.52)	3/8 (9.52)
	Suction	3/8 (9.52)	3/8 (9.52)	1/2 (12.7)	1/2 (12.7)	1/2 (12.7)	5/8 (15.9)	5/8 (15.9)	5/8 (15.9)
Drain Connections inches (mm)		3/4 (19.05)	3/4 (19.05)	3/4 (19.05)	3/4 (19.05)	3/4 (19.05)	3/4 (19.05)	9/8 (28.6)	9/8 (28.6)
Dimensions inches (mm)	Height	10 7/8 (275)	10 7/8 (275)	11 3/4 (298)	11 3/4 (298)	11 3/4 (298)	12 1/2 (319)	12 1/2 (319)	12 1/2 (319)
	Width	33 1/4 (843)	33 1/4 (843)	37 (940)	37 (940)	37 (940)	39 3/4 (1008)	39 3/4 (1008)	39 3/4 (1008)
	Depth	7 (180)	7 (180)	7 7/8 (200)	7 7/8 (200)	7 7/8 (200)	8 3/4 (221)	8 3/4 (221)	8 3/4 (221)
Net Weight Lbs (kgs)		10.1 (10)	10.1 (10)	28.7 (13)	28.7 (13)	28.7 (13)	33.1 (15)	33.1 (15)	33.1 (15)



Wireless Controller
VAEWP-R001 (Standard)



Wired Controller
VAECR-R001 (Optional)



Deluxe Wired Controller
VAEDC-R001 (Optional)



Smart Zone Controller
VAESC-R032T (Optional)



Centralized Controller
VAMCC-R255T (Optional)

- Notes:**
1. Nominal capacities are based on ARI standards 210/240-89, air entering the indoor coil operating at high fan speed for 220V-240V setting. Cooling: 80/67° F (27/19° C) DB/WB indoor & 95° F (35° C) outdoor ambient temperature.
 2. Refrigerant metering device is installed at the indoor unit as standard.

3. Flare fittings are provided for connecting indoor and outdoor units.
4. Insulation of both liquid and suction line is required (Heat Pump Mode).
5. For details of model number nomenclature, please refer to publication OGMNM-0315.

OMEGA
ENVIRONMENTAL
TECHNOLOGIES LLC.

17702 Mitchell North, #101
Irvine, CA 92614, USA
Tel: 714 795 2830
Fax: 714 966 1649
info@omegainverter.com
www.omegainverter.com



ISO 14001 ISO 9001

OTEC
AIR CONDITIONING
Showroom & Technology Center
11380 Interchange Circle North
Miramar, FL 33025 - USA
Tel: 305 731 2140, 888 840 7550
Fax: 954 212 8280
info@otecus.com
www.otecus.com